

ROGUE**Frame only without shock**

FRAME SIZE	EAN	SKU
S -size	6979246610455	ROFSMBAA
M -size	6979246610462	ROFMMBAA
L -size	6979246610479	ROFLMBAA
XL-size	6979246610486	ROFXMBAA

WHATS INCLUDED

Rogue carbon frame
 16T CNC idler with idler guide
 FSA No.57 ZS44/56 headset
 Rogue motor cover
 Rogue charge port cover
 12X148 rear thru axle
 UDH Hanger
 Bottle cage screws
 Seatpost clamp
 Cable lugs

Avinox M1 motor 250W 105Nm
 Avinox chainwheel spider with lock
 Avinox isis crank 155mm
 Avinox battery 36V 800Wh
 Avinox DP100 2inch smart screen
 Avinox BC100 bluetooth remoter X2
 Avinox speed sensor
 Avinox 4A 168Wh charger
 Avinox power cables
 Velduro steel chainwheel, 104BCD, 34T

SPEC SUITABLE LIST

Handle System

External wiring headset, ZS, dia top 44mm/
 bottom 56mm

Suspension System

1.5T, 160-180mm travel fork suitable, 170mm
 travel as suggest, CTA:584mm
 Shock 205mmX65mm(TR)*, bushing as M8*30mm
 65mm travel shock max to 172mm rear travel
 62.5mm travel shock as 160mm rear travel

Saddle System

Dia 31.6mm, Seatpost insert length:
 S:262mm, M:282mm, L: 302mm, XL:325mm
 Dropper cable length: 1200mm
 Dropper travel suggest as below
 S:180mm, M&L:210mm , XL:240mm

Brake System

Frame rear brake post mount 200mm directly
 Front brake cable 850mm
 Rear brake cable 1700mm

Drive System

Chainwheel: 104BCD, up to 36T
 Crank: up to 165mm length, Min offset:25mm
 UDH deralleur suitable
 1x shifting only
 Shimano and SRAM shift both fit
 e-shift and manual shift both fit
 Manual shift cable length 2000mm

Wheel System

Front hub: depends on the fork, normally 15X110mm
 Rear hub: 12X148 boost, 6-Bolts
 Front rim: 29'(700C) rim
 Rear rim: 29'(700C) or 27.5(650B) rim
 Front tire: depends on your fork
 Rear tire: max to 29'X2.4 or 27.5'X2.4